

# Suzuki TC-90R Blazer



Aluminum single-cylinder,  
rotary-valve engine



Famous 12 month/12,000 mile warranty\*

Wide bridge handlebars

Power tuned exhaust/spark arrester

Double cradle tube frame/skid plate


Deep cushioned dual passenger seat

Chrome luggage rack

High clearance fenders, front and rear

Long travel front forks

18" knobby tires



4 x 4 dual-range transmission

CCI automatic lube

Positive-acting brakes, front and rear

Length	73.8"
Width	33.1"
Height	42.5"
Wheel Base	47.0"
Ground Clearance	8.7"
Dry Weight	199 lbs.
Engine Type	2-stroke air-cooled aluminum single-cylinder rotary-valve
Bore & Stroke	1.85" x 2.04"
C. C.	89
Compression Ratio	6.7:1
Carburetor	VM19SC
Maximum Output	11 hp/7500 rpm
Maximum Torque	7.8 ft.-lbs./7000 rpm
Speed Range	60-65 mph
Transmission	4-speed dirt, 4-speed street
Clutch	Multi-plate, wet disc
Starter	Primary kick
Brakes: Front	Right hand, internal expanding
Rear	Right foot, internal expanding
Suspension: Front	Telescopic, oil-dampened
Rear	Swinging arm, oil dampened
Tires: Front	2.75-18-4PR
Rear	3.00-18-4PR
Color	Strip Orange, Aspen Yellow
Fuel Tank Capacity	1.6 gals.
Oil Tank Capacity	2.5 pts.
Instruments	Speedometer
Climbing Ability	35°

All prices and specifications subject to change without notice.



\*Covers all internal parts of cylinder head, block and transmission. Purchaser must comply with Owner's Manual Instructions: mail registration to Suzuki within 48 hours, and receive service checks from a franchised Suzuki dealer at 750, 2,000 and every 2,000 miles thereafter during warranty period.

## Suzuki: built to take on the country.

U.S. Suzuki Motor Corporation, Santa Fe Springs, California 90670

Part No. 99404-25000

Litho in USA



# Suzuki TS-90R Honcho



Famous 12 month/12,000 mile warranty\*

Optional "Hop-up" kit available. Boosts cc's to a "100"


Flat bridge moto-cross type handlebars

Power tuned exhaust/spark arrester

Flip-up seat

Moto-cross type forks

18" "Trials" tires



Aluminum rotary-valve engine

5-speed constant mesh transmission

Enduro type single leading shoe brakes

CCI automatic lube

Length	73.8"
Width	33.1"
Height	42.5"
Wheel Base	47.0"
Ground Clearance	6.8"
Dry Weight	197 lbs.
Engine Type	2-stroke air-cooled aluminum single-cylinder rotary-valve
Bore & Stroke	1.85" x 2.04"
C. C.	89
Compression Ratio	6.7:1
Carburetor	VM19SC
Maximum Output	11 hp/7500 rpm
Maximum Torque	7.8 ft.-lbs./7000 rpm
Speed Range	60-65 mph
Transmission	5-speed constant mesh
Clutch	Multi-plate, wet disc
Starter	Primary kick
Brakes: Front	Right hand, internal expanding
Rear	Right foot, internal expanding
Suspension: Front	Telescopic, oil-dampened
Rear	Swinging arm, oil-dampened
Tires: Front	2.75-18-4PR
Rear	3.00-18-4PR
Color	Pop Green, Daytona Blue
Fuel Tank Capacity	1.6 gals.
Oil Tank Capacity	2.5 pts.
Instruments	Speedometer
Climbing Ability	35°

All prices and specifications subject to change without notice.



\*Covers all internal parts of cylinder head, block and transmission. Purchaser must comply with Owner's Manual Instructions, mail registration to Suzuki within 48 hours, and receive service checks from a franchised Suzuki dealer at 750, 2,000 and every 2,000 miles thereafter during warranty period.

## Suzuki: built to take on the country.

U.S. Suzuki Motor Corporation, Santa Fe Springs, California 90670

Part No. 99404-25000

Litho in USA